

2020 RENEGADE® X® xc 650 T

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Anti-Lock Brake System (ABS)
- Front and rear FOX® PODIUM† 1.5 RC2 shocks
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshoot® ATR tires
- Front & central skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Torsional Trailing arm Independent (TTI) rear suspension
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



■ Black, Grey & Sunburst Yellow

ENGINES

650

Type	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	FOX† PODIUM† 1.5 RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	FOX† PODIUM† 1.5 RC2

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Seat	Standard
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
		Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, front & central skid plate, mudguards

WARRANTY

Factory	2 years
---------	---------

TIRES / WHEELS

Front Tires	ITP Holeshoot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshoot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlocks

DIMENSIONS / CAPACITIES

L x W x H	218.4 x 122 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	26.7 cm
Seat Height	87.7 cm
Dry Weight*	303 kg
Rack Capacity	Rear: 16 kg
Storage Capacity	N/A
Towing Capacity	660 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5 L

©2019 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN Viscodrives GmbH. *All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the vehicle Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Always remember that riding and alcohol/drugs don't mix. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

can-am



Can-AmOffroad.com