

### HIGHLIGHTS

- Rotax® V-twin engine
- Arched double A-arm front suspension with front sway bar
- Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,500-lb (1,588 kg) winch
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle† ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- Increased ground clearance
- Digitally Encoded Security System (D.E.S.S.™)
- High strength multi-functions racks with LinQ™ quick-attach accessory
- 21.4 L water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- Heated hand grips
- Mudguards
- Heavy duty front bumper



- Tundra Green / 570
- Boreal Green / 650 / 1000

ENGINES	570	650	1000
Type	48HP, Rotax V-twin, liquid cooled	59HP, Rotax 649.6 cc V-twin, liquid cooled	80HP, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
Speed Category	Up to 60 km/h		

### SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25,1 cm) travel
Rear Shocks	Oil

### TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

### BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

### DIMENSIONS / CAPACITIES

Estimated Dry Weight *	827 lb (375 kg)	827 lb (375 kg)	900 lb (408 kg)
L x W x H	94 x 48 x 53 in. (238.8 x 121.9 x 135 cm)		
Wheelbase	59 in. (149.9 cm)		
Ground Clearance	12 in. (30.5 cm)		
Seat Height	34.5 in. (87.7 cm)		
Rack Capacity	Front: 100 lb (45 kg) / Rear: 200 lb (90 kg)		
Storage Capacity	Rear: 5.7 gal (21.4 L)		
Towing Capacity	750 Kg trailer with brakes and 335 kg trailer without brakes		
Fuel Capacity	5.4 gal (20.5 L)		

### FEATURES

Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Protection	Heavy-duty front bumper Heated grips Mudguards

### WARRANTY

Factory warranty	2-years BRP limited warranty
------------------	------------------------------